Support Water Tender PRE-USE INSPECTION FORM Pass Fail

Company Name:		Date:		Page 1 of 2		
Vehicle Identification	Odometer Reading					
NWCG Type Tactical Water Tender (1-3): Allowable Tank Capacity (gallons)						
VIN #:						
License #:	State:					
Make: Model:		Year:				
All Wheel Drive		Yes		No		
Markings Posted on Vehicle (annotate actual posting)		Yes		No		
Company Name:						
Unit ID #:						
DOT #:						
Vehicle Licensing		•				
Vehicle meets licensing requirements		Yes		No		
Vehicle meets DOT or CVSA requirements (optional)		Yes		No		
Minimum Tender Inventory			atisfactory	<u>·?</u>		
		Yes	No	Qty		
1 – Handheld Programmable Radio						
1 − 1 ½" nozzle NH combination fog/straight stream						
1 − 1 ½" NH female to 1" NPSH male reducer						
1 – Shovels, size 0 or 1						
1 – Pulaskis						
1 – Spanner Wrench, combination 1 ½" to 2 ½ "						
1 – Adjustable Hydrant Wrench						
2 – Adapters 1 ½" NPSH Female to 1 ½" NH Male						
2 – Adapters 1 ½" NH Female to 1 ½" NPSH Male						
2 – Reducers 2 ½" NH Female to 1 ½" NH Male						
1 – Double Male 1 ½" NH						
1 – Double Female 1 ½" NH						
1 – Gated Wye 1 ½" NH						
1 – Fire Hose Clamp 2 ½"						
100' – 1 ½" cotton/synthetic hose NH thread						
50' – 2 ½" cotton/synthetic hose NH thread						
<u>Pump</u> PTO	A	Luxiliary	uxiliary			
Fuel to operate pump for 12 hours (If Auxiliary Pump)	uel to operate pump for 12 hours (If Auxiliary Pump)			No		
20' Suction hose w/strainer or screened foot valve w/ hole s	ize of 3/32" or less	Yes		No		
Discharge Outlets						
1 – 2 ½" NH		Yes		No		
2 – 1 ½" NH		Yes		No		
Spray Bar Configuration (Circle one)						
Gravity Front or Rear Gravity Front & Rear	Pressure Front or Rea	r Press	ure Front &	& Rear		
Additional Vehicle Items	•	Yes		No		
Reflective Triangles, bi-directional, set of 3						
Fire Extinguisher, 1 rated at 10 B:C or better						
1 – First Aid Kit (5 person)						
2 – each Wheel chocks						
1 – each Portable Hand Lights						
Seat Belt for all passengers						
4" Dump Valve at bottom of tank (min. 34" from round)						
Tires minimum 4/32" Front, 2/32" Rear tread						
Tire load ratings in accordance with vehicle GVWR						
Tank meets baffling requirements.						
Back up alarm						
•		•				

Company"					Page 2 of 2			
Personal Protective Equipment (check all inventoried)								
Fire Shelter	Nomex shirt/pants	Hardhat	Gloves		Boots			
Glass (chips/cracks)								
Body Condition (dents/scratches)								
	,							
Name of Contractor ((A	C: an atoms of C	4		Data			
Name of Contractor (type or print)	Signature of Co	<u>ontractor</u>		<u>Date</u>			
Name of Inspector (ty	pe or print)	Signature of In	spector		Date			
	• • ,							
<u>Inspectors' Agency</u> <u>Inspector's Phone #</u>								
Remarks: (Document	t all failed items)							
Kemarks. (Documen	t an fancu items)							